

X5i 5-25×56 P 1/4 MOA L BRM-|+ Specifications

Capacity

Type of build	zoomable magnification
Minimum magnification	5
Maximum magnification	25
Front lens diameter (mm)	56
Exit pupil	9.5 - 2.3
Exit pupil at min. enlargement (mm)	9.5
Exit pupil at max. enlargement (mm)	2.3
Eye relief (mm)	95
Diopter compensation	-3 / +2
Lens coating	fully, multiple
Type of mounting	Mounts not included in delivery
Central tube diameter (mm)	30

Field of view

No parallax over (m)	50 - ∞
100 m adjustment per clic	0.26 / 7.2
Twilight factor	15.5 - 37.4
Twilight factor at min. enlargement	37.4
Twilight factor at max. enlargement	15.5
Field of view at 100 m (m)	7 - 1.5
Field of view at min. enlargement (m)	7
Field of view at max. enlargement (m)	1.5
Reticle	BRM-I+
Reticle usage	Hunting

Special features

Illuminated reticle	yes
Automatic switch-off	-
Height adjustment	yes
Lateral adjustment	yes
Parallax adjustment	-
Bullet drop compensator	-
Integrated rangefinder	-
Protection cap	yes
Lens hood	-
Water-proof	yes
Dew protected	yes
Watertight	yes

General

Colour	matt black
Length (mm)	377
Weight (g)	910
Series	X5i

Area of application

Stalk hunting	good
Raised hide	very good
Drive hunting	good
Magnum caliber	very good
long distance	very good
Airgun (< 7,5 Joule)	-
Airgun (> 7,5 Joule)	-
handgun	-

